

MR8000 Semitrailer – Ready for delivery - Turkey

DRILLMEC MR8000 Semitrailer mounted, Rotary drilling & workover rig manufactured in accordance with API specifications, suitable to work at ambient temperature from -20°C to +50°C. Mast & Substructure manufactured in accordance API spec 4F (4th edition), PSL-1.
 Hazardous area distribution and extension compliant with API RP 500.

For more informations please contact Mr. Riccardo Bramucci (r.bramucci@drillmec.com)

<p>MR8000 Semitrailer Mounted</p>	<ul style="list-style-type: none"> • Drill pipe stands handling Range 2 (double) • Drawworks rated input 1080 HP – 805 kW • Static hook load / number of lines 440,000 lbs (200 metric ton) – 10 • Mast clear height from ground level 132 ft (40.2 m) • Mast clear height from drilling floor 115 ft (35 m) • Drilling floor height from ground level 17 ft (5.2 m) • Setback capacity 250,000 lbs (113 metric ton) • Casing capacity on rotary table beams 440,000 lbs (200 metric ton)
<p>Drawworks</p>	<p>Drillmec Double Drum Drawwork installed on semitrailer, one for main drum and other for sandline, complete with:</p> <ul style="list-style-type: none"> • Equalized band brakes • Hoisting speeds the same of diesel engine • Reverse speed • Crown-o-matic system device • Transmission between drawworks and auxiliary brake by chain
<p>TOP DRIVE</p>	<p>Drillmec Hydraulic top drive HTD250, with HPU diesel driven. Max speed: 189 rpm Max torque: 34.000 Nm</p>
<p>Other Equipment</p>	<p>Mud tanks c/w two Drillmec 1000 hp diesel driven mud pumps, Power system and MCC, well control equipment, rotary table, air system, drilling Instrumentation, etc..</p>